



Electrolux

Modular Cooking Range Line 700XP Half Module Electric Bain Marie Top

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux



Modular Cooking Range Line

700XP Half Module Electric Bain Marie
Top

371096 (E7BMEDB000)

700XP HALF MODULE
ELECTRIC BAIN MARIE TOP
- 230 V

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Maintains cooked food at serving temperature by using hot water inside the well. Water temperature controlled by thermostat with maximum temperature of 90 °C. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Bain Marie used for keeping cooked food at serving temperatures using hot water.
- Incoloy armoured heating elements positioned beneath the base of the well.
- Water basin is seamlessly welded into the top of the appliance.
- Filling water level is plate-marked on the side of the well.
- Unit to feature manual refill of well.
- Water temperature controlled by thermostat with maximum temperature value of 90 °C.
- Basin drained by tap on the front of the machine.
- All major compartments located in front of unit for ease of maintenance.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

- Support for bridge type installation, 400mm PNC 206154 ☐
- Water column with swivel arm (water column extension not included) PNC 206289 ☐
- Water column extension for 700 line PNC 206291 ☐
- Frontal handrail, 400mm PNC 216046 ☐
- Large handrail - portioning shelf, 400mm PNC 216185 ☐
- 2 side covering panels for top appliances PNC 216277 ☐
- Drilled false bottom half module for bain-marie PNC 921622 ☐


APPROVAL: _____




Electrolux

Modular Cooking Range Line 700XP Half Module Electric Bain Marie Top

Front




Top



D = Drain
EI = Electrical connection

Side



Electric

Supply voltage:

371096(E7BMEDB000)

230 V/1N ph/50/60 Hz

Total Watts:

1.5 kW

Water:

Water Drain:

2"(50 mm)

Key Information:

Usable well dimensions (width): 306 mm

Usable well dimensions (height): 156 mm

Usable well dimensions (depth): 510 mm

Thermostat Range: 30 °C MIN; 90 °C MAX

Net weight: 20 kg

Shipping weight: 25 kg

Shipping height: 520 mm

Shipping width: 460 mm

Shipping depth: 820 mm

Shipping volume: 0.2 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line
700XP Half Module Electric Bain Marie Top

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2012.09.28