

# GRIDDLE TOASTER 600mm

G55T

- Griddle plate with toaster under
- 16mm griddle plate
- Individually controlled dual burners
- Large capacity grease collection drawer
- Rear rollers
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



#### G55T

#### Overall Construction

- 16mm machined surface mild steel griddle plate
- 2.5mm stainless steel integral splashquard
- $\bullet$  2.5mm stainless steel grease channel at front of plate
- Stainless steel grease collection drawer below mid shelf
- Dual burners with individual pilot and flame failure
- $\bullet$  Stainless steel radiant reflectors on burners for efficient to asting
- Welded 1.5mm 304 stainless steel bull nose
- Splashback and hob sides 1.2mm 304 stainless steel
- Vitreous enamelled control panel
- $\bullet$  Toasting compartment 1.2mm high temperature aluminised steel
- Base shelf and mid shelf finished in 0.9mm 304 stainless steel
- Vitreous enamelled steel spill tray
- Chrome wire toasting rack with integral crumb tray
- Chrome wire rack supports
- 63mmdia.heavy-duty1.2mm304stainlesssteeladjustablelegsatfront and two rollers at rear

### Controls

- Large easy use control knobs heat resistant reinforced
- Easy view control settings on knobs
- Dual controls with variable high to low burner setting
- Flame failure pilot burners
- Piezo ignition to pilot burners

### **Cleaning and Servicing**

- $\bullet$  Removable grill rack system, rack supports, and crumb tray
- Removable grease drawer
- Easy clean stainless steel exterior
- Access to all parts from front of unit



# **GRIDDLE TOASTER 600mm**

G55T

#### **Specifications**

#### Burners

2 x 22MJ tubular burners with grill radiants

#### Gas power

44MJ/hr, 12.2kW

16mm thick mild steel Cooking surface 590mm x 520mm, 3068cm2

#### **Toaster Dimensions**

Rack size 430mm x 470mm Rack positions 4

#### Gas connection

 $R^{1/2}$  (BSP) male

Optional underside connection, please specify when ordering

All units supplied with Natural and LP gas regulator

#### **Dimensions**

Width 600mm

Depth 812mm

Height 915mm

Incl. splashback 1085mm

#### Nett weight

115kg

#### Packing data

0.70m3, 165kg

Width 645mm

Depth 870mm Height 1255mm

Gas types

### Available in Natural gas and LP gas, please specify

when ordering


Units supplied complete with gas type


conversion kits

Other gas types on request

#### Options

. Adjustable feet at rear Joining caps Castors







## **MOFFAT**

#### moffat.com.au moffat.co.nz

Australia moffat.com.au

#### Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

#### New Zealand moffat.co.nz

#### **Moffat Limited**

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





IS09001 Quality Management



Cert. No. 6869

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.01.19/1620