NAME #

SIS#

AIA#



Modular Cooking Range Line

700XP 22 It. Gas Multifunctional

Cooker with compound bottom

Modular Cooking Range Line

Electrolux

700XP 22 It. Gas Multifunctional Cooker with compound bottom

371106 (E7MFGHDI00)

700XP GAS MULTIFUNCTIONAL COOKER 22 LT - WITH COMPOUND BOTTOM

# **Short Form Specification**

#### Item No.

Suitable for natural gas or LPG. Burners with double flame line to guarantee heat uniformity. To be installed on 50 mm high feet for cleaning ease. Well to have rounded corners and cooking surface in compound steel (a 3mm layer of 316 AISI stainless steel on top of a 12mm layer of mild steel). Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

## Main Features

- Multi purpose cooking appliance that can be used to shallow fry, cook liquids or even as a bain marie. Unit can be used for sautéing, poaching, steaming, simmering, stewing, braising, boiling and preparing white sauces.
- Well cooking surface made in compound steel (a 3mm layer of 316 AISI stainless steel on top of a 12mm layer of mild steel) for optimum grilling results.
- The stainless steel well to have rounded corners to facilitate cleaning.
- Bottom temperature control is precisely set by a thermostat on the control panel.
- Temperature can be set from 100 °C to 250 °C.
- Uniform temperature distribution over the whole base.
- Short heat-up time of the empty pan.
- Burners equipped with double flame line for better heat distribution.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

## Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

# Included Accessories

• 1 of Scraper for smooth plate fry tops	PNC 164255
<ul> <li>1 of Blades with rounded sides for</li> </ul>	PNC 921694
scraper for multifunctional cookers	

### Optional Accessories

Pair of side kicking strips for concrete

Draught diverter, 150 mm diameter	PNC 206132
Matching ring for flue condenser, 150 mm diameter	PNC 206133
Flanged feet kit	PNC 206136
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210
<ul> <li>2 supports with side runners for 4 GN 1/1 containers for open base cupboards (multifunctional cookers, solid top and gas ranges with cupboard)</li> </ul>	PNC 206244
<ul> <li>Pair of side kicking strips</li> </ul>	PNC 206249

APPROVAL:

PNC 206265

installation



# Modular Cooking Range Line 700XP 22 It. Gas Multifunctional Cooker with compound bottom


• Pressure regulator for gas units


PNC 927225 🖵





# Modular Cooking Range Line 700XP 22 It. Gas Multifunctional Cooker with compound bottom






688 mm

56 mm

#### G = Gas connection

2 3/16





### Gas

Gas Power:

371106(E7MFGHDI00) 47726 Btu/hr (14 kW) **Gas Type Option:** LPG:Natural Gas Gas Inlet: 1/2" NPT

Natural gas - Pressure: 7" w.c. (17.4 mbar) LPG Gas Pressure: 11" w.c. (27.7 mbar)

# Key Information:

Working Temperature MIN: 100 °C **Working Temperature MAX:** 250 °C 80 kg Net weight: Shipping weight: 95 kg Shipping height: 1140 mm Shipping width: 900 mm Shipping depth: 820 mm Shipping volume:  $0.84 \, m^3$ 

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Modular Cooking Range Line 700XP 22 It. Gas Multifunctional Cooker with compound bottom