

P1RS 16 Tray Reach-in Prover**P2RS** 32 Tray Reach-in Prover

P1RS

Product Features

- Full stainless steel construction internal and external
- Swing door fitted as standard
- Easy to use electronic panel
- Fitted with 16 removable tray slides
- 75mm gap between tray slides
- Humidity adjustable up to 100%
- Suitable for trays sized 450mm x 760mm and 405mm x 760mm
- LED light
- Temperature adjustable up to 40°C
- Supplied on wheels

Reach-in Prover for precision fermentation

P1RS

16 Tray Reach-in Prover

Model P1RS

Dimensions

Width	580mm
Depth	940mm
Height	2000mm

Electrical Requirements

Single phase, 240V, 50Hz, 15 amp

Nett Weight 100kg

Model P2RS

Dimensions

Width	1100mm
Depth	940mm
Height	2000mm

Electrical Requirements

Single phase, 240V, 50Hz, 15 amp

Nett Weight 135kg

Additional Technical Information

Dimensions EXCLUDE all protrusions - door handles, drain exits etc.

Minimum Ceiling Height required - 2200mm

Units require the following:

Drain Outlet

1/2" BSP Inlet

moffat.com.au

moffat.co.nz

Australia

moffat.com.au

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road
Mulgrave, Victoria 3170
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au

New South Wales

Telephone +612-8833 4111
nswsales@moffat.com.au

South Australia

Telephone +613-9518 3888
vsales@moffat.com.au

Queensland

Telephone +617-3630 8600
qldsals@moffat.com.au

Western Australia

Telephone +618-9413 2400
wasales@moffat.com.au

New Zealand

moffat.co.nz

Moffat Limited

Rolleston

45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150
sales@moffat.co.nz



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
AN.P.01.19

